

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. **Identification code of the product-type****LE-H66037-03** **Difuplan ERS 330 SK****Purpose**

- Underlay for discontinuous roofing
- Underlay for discontinuous roofing

Name, contact producer

BÜSSCHER & HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

system3

EN 13859-1:2014

Harmonized standard

EN 13859-1:2014

Declared performance

Essential characteristics	Performance	Harmonized technical specification
Fire classification	E	EN 13859-1:2014
Resistance to water penetration	W1	EN 13859-1:2014
Artificial aging - resistance to water penetration	NPD	EN 13859-1:2014
sd-value	0,14 (+0,02 / -0,06) m	EN 13859-1:2014
Tensile force long./trans.	440 / 380 (±40) N/50mm	EN 13859-1:2014
Artificial aging - Tensile force long./trans.	360 / 300 (±30) N/50mm	EN 13859-1:2014
Elongation (long./trans.)	50 / 60 (±20) %	EN 13859-1:2014
Artificial aging - Elongation (long./trans.)	≥ 65 / ≥ 65 %	EN 13859-1:2014
Resistance to tearing (long./trans.)	390 / 430 (±30) N	EN 13859-1:2014
Flexibility at low temperatures	- 40 °C	EN 13859-1:2014

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by



Bmstr. Dipl. Ing. Karl Landl

General Manager

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.