

H 96080

# Anschlussmanschette NW 110, mit Schrumpfschlauch

<b>Product</b>	Connection collar for the pass through of pipes, cables, conductions, fixings etc. at roof and basement waterproofings
<b>Application</b>	Torch-on method. The upper end is protected against water by the enclosed shrink tube.
<b>Remarks</b>	Further dimensions on request.

<b>Characteristics</b>	<b>Unit</b>	<b>Result</b>
Height	mm	320
Inside diameter	mm	117
Outside diameter	mm	125
Collar diameter	mm	500 x 500
Shrink tube length	mm	ca. 200
Shrink tube diameter	mm	140/42
shrinkable to	mm	42

The declared data are indices based on the statistical quality control and refer to the date of production. Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method. All specifications are without obligation. The user must assess the suitability of the product for the particular purpose and ensure the user's access to the current version of the product data sheet.

**Subject to alteration without notice.**

Storage conditions: The products have to be stored in original packaging, being protected from direct sun light, UV-beams and extreme conditions like heat, frost, moisture, etc. During cold season store the products in a frost-free area (+5°C) for 12 hours before application.

**Development, Production and Sales of our products according to ISO 9001.**